

ZKD-SC02-i3A Series Interactive Whiteboard

ZKDigimax's 4K digital interactive whiteboard is designed to enhance the sharing of inspirational knowledge in business and educational environments. The integrated meeting solution of the SC02-I365/75/86A product offers screen sharing, whiteboard writing, and remote video conferencing, which strengthens collaboration.



Key Features



4K UHD Display
3840X2160pixels



Split screen
Support split screen display



Built-in UHD Camera
48-megapixel



Dual System
Android 14
Windows 11 (optional)
Compatible with OPS



8 Microphones Array
8m of detection distance



Support NFC

Specifications

General

Model	SC02-I365A	SC02-I375A	SC02-I386A
Panel			
Screen Size	65 inch	75 inch	86 inch
Panel Type	ADS	ADS	IPS
Backlight	D-LED		
Resolution	3840 × 2160 (pixels)		
Aspect Ratio	16 : 9		
Brightness (typ.)	450cd/m ² (typ.)		
Contrast Ratio (typ.)	1200:1 (typ.)		
Viewing Angle	178°(H) / 178°(V)		
Refresh Rate	60Hz		
Response Time	8ms		
Glass Hardness	9H (Pencil) 7 (Mohs)		
Glass Type	Anti-glare		
Backlight Life (typ.)	50,000 hrs (min.)		
Touch			
Touch Technology	High Precision IR		
Touch Points	Up to 50		
Touch Response time	≤3ms		
Touch Accuracy	Center 90% touch area: ±1mm		
Touch Object Recognition Range (Min)	Single touch: ≥1.4mm Multiple touch: ≥2.0mm		
Writing Height	≤1mm		
System			
CPU	Quad core A73+Quad core A53		
GPU	MaliG52 MP8		
Memory	8GB		
Storage	128GB		
Operating System	Android 14		
Connectivity			
Front Port	USB 3.0x2 Type-C(65W)x1		
Bottom Port	AUDIO Inx1 VGAx1 LAN IN / OUTx2 RS232X1 MIC Inx1 HDMI OUTx1 AUDIO OUTx1 SPDIFx2		
Side Port	Touch-USBx2 DPX1 HDMI IN (ARC) 1 2.0x1 HDMI IN (CEC) 2 2.0x1 Type-Cx1 USB 2.0x1 USB 3.0x2 OPS slot (for slot-in PC)x1		

General

Built-in peripherals			
Wi-Fi		Wi-Fi 6: 802.11 ax/b/g/n/ac	
Bluetooth		BT 5.0: 2.1+EDR/4.2/5.0	
NFC		ISO / IEC 14443 A / ISO / IEC 14443 B	
Camera	Pixel	Pixel 48 Mega pixels	
	FOV	FOV Diagonal 114.9°	
	Face tracking	Support	
	Sound Localization	Support	
Microphone	Array Quantity	8 microphones array	
	Pickup Range	Support	
	3D Noise Reduction	Support	
	AEC & AGC	Support	
Speaker		2 20W+1 20W(Subwoofer optional)	
Power			
Operating Power		100 V ~ 240 V/AC, 50/60 Hz	
Standby Power Consumption		<0.5W	
Power Consumption(typ.) (100% Brightness)		178W	215W 278W
Physical			
Dimensions (W × H × D)		1483.9 86.7 911.6mm	1705 86.9 1036mm 1950.4 86.9 1174mm
Package Dimensions (L × W × H)		1640 185 1010mm	1860 185 1125mm 2095 185 1265mm
Net Weight (kg)		40.5kg	53.95kg 66.85kg
Weight with Packaging (kg)		50.2kg	64.5kg 79.05kg
Case Material		Aluminium Alloy and Sheet Metal	
Color		Blue grey	
Environment			
Operating Temperature		0°C to 40°C	
Storage Temperature		10°C to 60°C	
Operating Humidity		20% to 80% RH (Non-condensing)	
Storage Humidity		10% to 60% RH (Non-condensing)	
Accessories			
Cables		Power Cable 1, USB Cable 1, HDMI Cable 1	
Remote Controller		1	
Wall Mount		1	
Stylus Pen		2	
Eraser		1	
Peripheral Accessories(Optional)			
Movable Bracket		YES	
OPS		YES	
Wireless Dongle		YES	