



DG01-A6P18/25

LED POSTER DISPLAY

Our LED poster screen is a sleek and versatile digital billboard designed to showcase your core products with ease. With the ability to upload videos and digital content effortlessly, it's the perfect solution for dynamic advertising. Stylish, portable, and easy to maintain, our LED poster screen can be placed anywhere to capture attention and elevate your brand.

Key Features



800 Nits



3840 Hz



Wireless
Control



USB

Applications



Exhibition Halls



Hotel



Malls



Town Square

Specifications

General

Model	DG01-A6PI8	DG01-A6P25
Pixel Pitch	1.8mm	2.5mm
Module Size	320 x 160mm	320 x 160mm
Module Resolution	170 x 85dots	128 x 64dot
LED Configuration	SMD 3 in 1	SMD 3 in1
Module Structure	SMD1515	SMD2121
Display Dimension	1920 x 640mm	1920 x 640mm
Cabinet Size	2008*652*450mm	2008*652*450mm
Frame Material	Steel	Steel
Frame Color	Black (default)	Black (default)
Weight	45kg / unit (approx..)	45kg / unit (approx..)
Brightness	≥800nit	≥800nit
Viewing Angle	160° H; 140° V	160° H; 140° V
Refresh Rate	3840Hz	3840Hz
Contrast Ratio	125.0006944	125.0006944
Operation Power	AC110 / 240V, 50-60Hz	AC110 / 240V, 50-60Hz
Max Power	800W / m ²	600W / m ²
Average Power	240W / m ²	180W / m ²
Connection Type	USB Disk / Wi-Fi	USB Disk / Wi-Fi
Supported Media Files	Video / Photo	Video / Photo
Operating Temperature	-10°C-+40°C	-10°C-+40°C
Storage Temperature	-20C-+55C	-20°C-+55°C
Operating Humidity	10-65% RH. No Condensation	10-65% RH. No Condensation
Storage Humidity	10-90% RH. No Condensation	10-90% RH. No Condensation
Operating Lifetime	100.000 Hours	100.000 Hours