



DG03-B1F-Series

43" | 55" OUTDOOR DRIVE-THRU DISPLAY

Our digital outdoor display is perfect for drive-thrus, offering a bright, weatherproof solution designed to enhance customer experience. Its high visibility in all lighting conditions ensures clear menu display, while durable construction protects against the elements. Ideal for fast food restaurants and retail, it provides seamless integration with dynamic content management, making menu updates and promotions effortless.

Key Features



IP Rating: IP65

With an IP55 rating, our digital outdoor display offers superior protection against dust and water, ensuring reliable performance in challenging environments.



Low Maintenance

Designed for low maintenance, our digital outdoor display requires minimal upkeep while delivering reliable performance and clear visuals.



24/7 Performance

Our digital outdoor display delivers 24/7 performance with reliable, high-quality visuals.



Optimized Heat Dissipation System

Ensures consistent performance by effectively managing heat, even in demanding conditions.



Advanced Content Management System

Our CMS offers seamless control over your digital signage, enabling easy scheduling, updates, and customization. With a user-friendly interface and powerful features, it ensures your content is always fresh, engaging, and perfectly tailored to your audience.

Specifications

General

Mainboard	OS	Android 11.0
	CPU	Quad Core Cortex-A55 2.0GHz
	Chipset	RK3568
	RAM	2GB
	ROM	16GB
Display	Size	55-inch
	Aspect Ratio	16:9
	Display Colors	8bits (16.7M)
	Resolution	1920 × 1080
	Contrast	4000:1 (Dynamic)
	View Angle	178° (H)/178° (V)
	Brightness	2500cd/m ² (typ.)
Speaker	Power	8 Ω 10W
Interface	RJ45	1
	Earphone	1
	USB 3.0	1
	USB OTG	1
	HDMI OUT	1
	TF Card	1
Support Format	Video	wmv/avi/flv/rm/rmvb/mpeg/ts/mp4
	Audio	MP3/WMA/MP2/WAV
	Image	BMP/JPEG/PNG/GIF
Network	Wi-Fi	Support
	LAN	RJ45
Power	Power Input	AC 100~240V 50/60Hz
	Max Consumption	400W
Physical Parameters	Product Dimensions	2000×830×400mm (L×H×W)
General Environment	Operating Temperature	-10°C to 50°C
	Storage Temperature	-20°C to 60°C
	Operating Humidity	5% to 90% RH (Non-condensing)
	Storage Humidity	5% to 100% RH (Non-condensing)

Dimensions

43 inch



55 inch

